#318 MINI AUDIOSTIX:

THE SWITCHCRAFT® #318 MINI AUDIOSTIX IS USED TO CONNECT DEVICES SUCH AS LAPTOPS AND MP3 PLAYERS TO HOUSE SOUND SYSTEMS IN CONFERENCE ROOMS AND AUDITORIUMS.

THE 3.5mm (1/8" MINI) STEREO INPUT IS CONVERTED TO A SINGLE MONO XLR OUTPUT. TRANSFORMER ISOLATION PROVIDES IMMUNITY FROM HUM & BUZZ CAUSED BY GROUND LOOPS AND RF INTERFERENCE.

ADDITIONAL FEATURES INCLUDE A VOLUME CONTROL FOR QUICK LEVEL CHANGES AND A GROUND LIFT SWITCH FOR ELIMINATING NOISE ISSUES COMMON WITH CONSUMER AUDIO DEVICES.

FEATURES:

- - 3.5mm, 26 AWG, 3 FOOT LONG CABLE

 - 3.5mm (1/8" MINI) STEREO INPUT BALANCED, MONO, MIC-LEVEL XLR OUTPUT
 - **VOLUME CONTROL**
 - **GROUND LIFT SWITCH**
 - ALL METAL HOUSING
 - TRANSFORMER ISOLATION
 - PASSIVE, NO POWER REQUIRED

 - OUTPUT LEVEL: -23dB (MIC LEVEL) FREQUENCY RESPONSE: 20Hz 20kHz (+/-3dB)
 - MADE IN CHICAGO, USA

CONTROLS:

 \rightarrow

INPUT - 3.5mm (1/8"):

ACCEPTS UNBALANCED STEREO SIGNALS FROM HEADPHONE OUTPUTS AND LINE SOURCES SUCH AS LAPTOPS AND MP3/CD PLAYERS.

OUTPUT - MALE XLR:

COMBINES THE LEFT AND RIGHT STEREO INPUT INTO A MONO, TRANSFORMER ISOLATED, BALANCED MIC LEVEL OUTPUT.

VOLUME CONTROL (KNOB):

USE TO REDUCE OUTPUT SIGNAL TO DESIRED LEVEL.

LIFT/GND (SLIDE SWITCH):

GROUND LIFT SWITCH. DISCONNECTS GROUND (PIN-1) CONNECTION BETWEEN INPUT AND ISOLATED OUTPUT XLR. USE TO BREAK GROUND LOOPS TO FURTHER REDUCE HUM & BUZZ.

NOTES:

- 1. XLR OUTPUT IS WIRED PIN-1 GROUND, PIN-2 HOT, AND PIN-3 COLD
- 2. MATERIALS:

JACK 3.5mm

HOUSING - THERMOPLASTIC, BLACK BUSHING - COPPER ALLOY, NICKEL PLATED SPRINGS - SPECIAL COPPER ALLOY, TIN PLATED

XLR CONNECTOR MALE


HOUSING - ZINC ALLOY, NICKEL PLATED CONTACTS - COPPER ALLOY, GOLD PLATED

HOUSING - ALUMINUM, RED ANODIZED

3.5mm CABLE (NOT SHOWN)
PLUG - BRASS AND STEEL, NICKEL PLATED

CABLE JACKET - PVC BLACK

3. THIS PRODUCT IS RoHS COMPLIANT.



(CUSTOMER DRAWING)

							_										
												OPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED FIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.					
						UNLESS OTHERWISE SPECIFIED	SIZE	W	VIDTH	MULT		LBS/M		TEM	PER		
						1. ALL DIMENSIONS IN INCHES [mm]	FINISH				MATERIAL						
						- TWO PLACE DECIMALS ±0.02 [0.5]	SPEC No.				SPEC No).					
	С	28499	5/18/22	TJK	TJK	- THREE PLACE DECIMALS ±0.005 [0.13]	FIRST U	N .	SCALE 1:1			\[\(\)			®		
	В	27808	11/16/16	PC	TJK		DATE DRAWN	BY	CHKD	APVD			JUU				
ł		07505	05/00/45		T 114		11/17/11	ВНМ	TJK	TJK						_	
	Α	27505	05/28/15	PC	TJK	-	11/17/11	Di iivi	06/15/16	06/15/16		SHEET	1	OF	1		
	REV	ECO NUMBER	DATE	BY	APVD		NAME MINI AUDIOSTIX				PART No		_		RE\		
	REVISIONS					DO NOT SCALE DRAWING	3.5mm JACK - XLR ADAPTER, RoHS				318				C		