



NOTES:

1. CABLE RANGE: \varnothing 0.236-0.354 [6.0 - 9.0]
2. RECOMMENDED MOUNTING HOLE: \varnothing 0.656 [16.67].
3. IP68 RATED WHEN PROPERLY ASSEMBLED. IMMERSED IN 1.8M WATER FOR 24 HOURS.
4. ALL PARTS SHIPPED ASSEMBLED.
5. MATERIALS:
 SEAL NUT, CLAMP NUT, HEX NUT - BLACK, THERMOPLASTIC UL746C (F1) UV RATED
 GASKET AND SEAL RING - BLACK, EDPM RUBBER
6. THIS PRODUCT IS RoHS COMPLIANT.

SECTION A-A
CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.					
					SIZE	WIDTH	MULT	LBS/M	TEMPER	
					FINISH			MATERIAL		
					SPEC No.			SPEC No.		
					FIRST USED ON		SCALE 1.5:1			
C	28375	03/30/21	PC	TJK	DATE DRAWN	BY	CHKD	APVD	Switchcraft [®]	
B	28315	09/09/20	PC	TJK	4/30/20	FM	FM	TJK		
A	28308	07/31/20	PC	TJK	4/30/20	FM	4/30/20	7/2/20		
REV	ECO NUMBER	DATE	BY	APVD	NAME M16 x 1.5 CABLE GLAND, CABLE RANGE \varnothing 6.0 - 9.0mm				PART No. CGM16N35	REV C
REVISIONS					DO NOT SCALE DRAWING					