



NEW PRODUCT BULLETIN 660

SD104QA

# 4-CHANNEL DANTE OUTPUT BOX



**Switchcraft®**  
**Pro Audio**



Rubber corners protect unit from handling damage

Compatible with standard RJ45 connectors or locking-style

Can be powered by external power supply or POE

Rugged and lightweight aluminum chassis

High quality, shielded Switchcraft XLRs

6 bright status LEDs provide detailed system feedback

## NEW SD104QA

**THE DANTE BOX THAT'S BUILT TO LAST** Since 1946, Switchcraft products have been known for their durability, and this new Dante box combines that approach with the latest Dante technology. Rugged rubber corners protect the Switchcraft XLRs outside and high quality electronics inside while maintaining a compact and lightweight form factor.



**4 ANALOG XLR  
BALANCED OUTPUTS**

4 Male XLRs (1 front, 3 back) are ESD protected and unbalanced compensated for professional quality audio.



**RUNS ON P.O.E OR  
48V DC POWER**

A standard DC power input provides added flexibility for situations where POE is unavailable or unreliable.



**SWITCHCRAFT  
QUALITY**

Assembled in Chicago in a rugged metal housing with rubber corners this unit is designed to handle abuse.

PARAMETER	PERFORMANCE	NOTES
Output Level	7 dBu	At 0 dBFS input, Balanced and single ended.
Frequency Response	10Hz to 20KHz flat within 0.3 dB	Measured with balanced output.
Network	Dante, AES67	
THD+N	<0.006%	At max output, A-Weighting.
Sampling rate	44.1, 48, 88.2 and 96KHz	
Bit depth	16, 24	
Power of Ethernet	Class 1 IEEE 802.3af PoE	
Weight	1.1 pounds	